



NS21-FJ-4HESI

NS21-FJ-5HESI

NS21-FJ-10DREHSI

فیوز خور

CERTIFICATION	CQC/CE/RoHS	CQC/CE/RoHS	CQC/CE/RoHS
MATERIAL			
Size(mm)	8.2x58x45	8.2x72.5x56.5	12x62x57.2
Screw	M3, Zinc-Coated Steel	M3, Zinc-Coated Steel	M4, Zinc-Coated Steel
Pressure Frame	Nickel-Coated Brass	Nickel-Coated Brass	Nickel-Coated Brass
Conductor	Nickel-Coated Brass	Nickel-Coated Brass	Nickel-Coated Brass
Housing	PA66/V-0	PA66/V-0	PA66/V-0
ELECTRICAL DATA			
Standards	IEC 60947-7-3	IEC 60947-7-3	IEC 60947-7-3
Max Voltage(V)	500*	800*	500*
Max Current(A)	6.3*	6.3*	6.3*
WIRING DATA			
Fuse Type	G / 5 x 20	G / 5 x 20 / 5 x 25 / 5 x 30	G / 5 x 20
Strip Length(mm)	9	8	11
Flexible Wire(mm ²)	0.5~4	0.2~4	0.5~16
Rigid Wire(mm ²)	0.5~6	0.2~4	0.5~16
Imperial Wire(AWG)	20~10	28~10	22~6
Torque(N·m)	0.5~0.6	0.5~0.8	1.5~1.8
PACKING			
Pcs/Inner Box	-	45	40
Pcs/Master Carton	-	765	800
ACCESSORIES			
End Plate			
Model	D-4HESI	-	-
Thickness	2.2mm	-	-
Pcs/Bag	100	-	-
* اطلاعات الکتریکی به نوع فیوز وابسته است			
Marking Tag			
ZB8	Pcs/Bag	100	Pcs/Bag
			100
			Pcs/Bag
			100

