



NS21-FJTK-S



NS21-FJ-5MTK

چاقویی و تست

CERTIFICATION	CQC/CE/RoHS	CQC/CE/RoHS	
MATERIAL			
Size(mm)	8.2x72x51.5	6.2x51x46.5	
Screw	M4, Nickel-Coated Brass	M3, Zinc-Coated Steel	
Pressure Frame	Nickel-Coated Brass	Nickel-Coated Brass	
Conductor	Nickel-Coated Brass	Nickel-Coated Brass	
Housing	PA66/V-0	PA66/V-0	
ELECTRICAL DATA			
Standards	IEC 60947-7-1	IEC 60947-7-1	
Voltage(V)	400	800	
Current(A)	57	16	
WIRING DATA			
Strip Length(mm)	13	8	
Flexible Wire(mm ²)	0.5~6	0.2~4	
Rigid Wire(mm ²)	0.5~10	0.2~4	
Imperial Wire(AWG)	26~10	18~10	
Clamping Screw	M4/1.2~1.5N·m	-	
Disconnecting Screw	M3/0.6~0.8N·m	-	
Torque (N.m)	-	0.5~0.6	
PACKING			
Pcs/Inner Box	45	40	
Pcs/Master Carton	765	2400	
ACCESSORIES			
End Plate			
Model	D-FJTK	-	-
Thickness	2mm	-	-
Pcs/Bag	100	-	-
Fixed Bridge			
Model	FB10-RTK/S	-	-
Max Current	41A	-	-
Pcs/Bag	10	-	-
Insertion Bridge			
Model	-	-	EB10-6
Max Current	-	-	12A
Pcs/Bag	-	-	10
Marking Tag			
	ZB8	100 Pcs	ZB6 100 Pcs



مدل تست



مدل چاقویی