


NS21-FJKKB2.5



NS21-FJKK3



NS21-FJKK5

دو طبقه

CERTIFICATION	CQC/CE/RoHS	CQC/CE/RoHS	CQC/CE/RoHS			
<b>MATERIAL</b>						
Size(mm)	5.2x62x48	5.2x56x62	6.2x56x62			
Screw	M3, Zinc-Coated Steel	M3, Zinc-Coated Steel	M3, Zinc-Coated Steel			
Pressure Frame	Nickel-Coated Brass	Nickel-Coated Brass	Nickel-Coated Brass			
Conductor	Nickel-Coated Brass	Nickel-Coated Brass	Nickel-Coated Brass			
Housing	PA66/V-0	PA66/V-0	PA66/V-0			
<b>ELECTRICAL DATA</b>						
Standards	IEC 60947-7-1	IEC 60947-7-1	IEC 60947-7-1			
Voltage(V)	500	500	500			
Current(A)	24	24	32			
<b>WIRING DATA</b>						
Strip Length(mm)	7	8	8			
Flexible Wire(mm <sup>2</sup> )	0.2~2.5	0.2~2.5	0.2~4			
Rigid Wire(mm <sup>2</sup> )	0.2~4	0.2~4	0.2~4			
Imperial Wire(AWG)	28~12	28~12	28~10			
Torque(N·m)	0.5~0.6	0.5~0.6	0.6~0.8			
<b>PACKING</b>						
Pcs/Inner Box	40	100	80			
Pcs/Master Carton	2400	2000	1600			
<b>ACCESSORIES</b>						
<b>End Plate</b>						
Model	D-FJKKB2.5		D-FJKK3/5		D-FJKK3/5	
Thickness	2.2mm		2.5mm		2.5mm	
Pcs/Bag	100		100		100	
<b>Fixed Bridge</b>						
Model	FBRN10-5N		FBRN10-5N		FBI10-6	
Max Current	22A		28A		32A	
Pcs/Bag	20		20		20	
<b>Insertion Bridge</b>						
Model	EB10-5		EBL10-5		EB10-6	
Max Current	20A		22A		28A	
Pcs/Bag	10		10		10	
<b>Small Partition&amp;Spacer Plate</b>						
TS-KK3	Pcs/Bag	200	Pcs/Bag	200	Pcs/Bag	200
DP-FJKKB2.5/3.5		100		100		100
DG-FJKK3/5		100		100		100
<b>Marking Tag</b>						
	ZB5	100 Pcs	ZB5	100 Pcs	ZB6	100 Pcs